

Helium. Pure Gas.

Description Helium is a rare atmospheric gas which is colorless, odorless, tasteless, nontoxic, nonflammable and only slightly soluble in water. The concentration of Helium in the atmosphere by volume percent is 5.24×10^{-4} . Helium is principally shipped and used in either gaseous or liquid form for nuclear reactors, semiconductors, lasers, light bulbs, superconductivity, instrumentation, medical applications, cryogenics, MRI and R & D laboratory research. Linde Gases Material Safety Data Sheets (MSDS) are available for Helium gas and should be used as guidelines in regard to first aid, methods of storage, handling and general use of Helium.

Purity specifications (Maximum impurity levels)*

Contaminant	Research Grade 99.9999%	UHP Grade 99.999%
Argon (Ar)	0.1 ppm	3.0 ppm
Carbon Dioxide (CO ₂)	0.1 ppm	1.0 ppm
Carbon Monoxide (CO)	0.5 ppm	1.0 ppm
Hydrogen (H ₂)	0.5 ppm	3.0 ppm
Krypton (Kr)	0.1 ppm	1.0 ppm
Neon (Ne)	0.5 ppm	3.0 ppm
Nitrogen (N ₂)	0.1 ppm	3.0 ppm
Oxygen (O ₂)	0.1 ppm	1.0 ppm
Total Hydrocarbons (THC)	0.1 ppm	1.0 ppm
Water (H ₂ O)	0.2 ppm	1.0 ppm

*Higher purities are available upon request.

Cylinder information

Purity	Cylinder Size*	Valve Outlet*	Volume Cu. Ft./Liters	Gross Weight Lbs/Kg	Pressure Psig/Bar
Research Grade	300	580	291/8200	139/63	2640/183
	200	580	243/6900	118/54	2490/173
	80	580	073/2100	048/22	2200/153
	LB	580/170	002/0057	006/03	1800/125
UHP Grade	300	580	291/8200	139/63	2640/183
	200	580	243/6900	118/54	2490/173
	80	580	073/2100	048/22	2200/153
	LB	580/170	002/0057	006/03	1800/125
Non-Refillable Cylinders	320	580	___/ 400	18/8	1625/113
	330	580	___/ 200	12/5	1250/087
	330	580	___/ 100	10/4	600/42
	340	580	___/ 50	7/3	725/51
	340	580	___/ 25	7/3	350/25

*Additional cylinder sizes and/or valve outlets are available upon request.

Physical constants

Chemical name		He
Molecular weight		4.00
Density of the gas at 70°F (21,1°C), 1 atm		0.0103 lb/ft ³ , 0.165 kg/m ³
Specific gravity of the gas at 70°F (21,1°C), 1 atm		0.138
Specific volume of the gas at 70°F (21,1°C), 1 atm		97.09 ft ³ /lb, 6.061 m ³ /kg
Density of liquid at boiling point and 1 atm		7.802 lb/ft ³ , 124.98 kg/m ³
Boiling point at 1 atm		-452.1°F, -268.9°C
Melting point at 1 atm		None
Critical temperature at 1 atm		-450.3°F, -267.9°C
Critical pressure		33.0 psia, 2.27 bar
Critical density		4.347 lb/ft ³ , 69.64 kg/m ³
Latent heat of vaporization at normal boiling point		8.72 Btu/lb, 20.28 kJ/kg
Latent heat of fusion at triple point		No Triple Point
Specific heat of the gas at 70°F (21,1°C), 1 atm	Cp	1.24 Btu/(lb) (°F) 5.19 kJ/(kg) (°C)
	Cv	0.745 Btu/(lb) (°F) 3.121 kJ/(kg) (°C)
Ratio of specific heats (Cp/Cv)		1.66
Solubility in water, vol/vol at 32°F (0°C)		0.00694
Weight of liquid at boiling point		1.043 lb/gal, 125.0 kg/m ³

Shipping data

Synonyms		He
CAS Register Number		7440-59-7
DOT Classification		Nonflammable gas
DOT Label		Nonflammable gas
Transport Canada Classification		2.2
Substance Identification (SI)		1046
UN Number		UN 1046
Hazards		High Pressure and suffocation
Toxicity (TL V)		Asphyxiant
Flammability Range (in air)		Nonflammable gas
Odor		None

Linde Electronics and Specialty Gases

One Greenwich Street, Suite 100, Stewartville, NJ 08886

Phone +1.908.329-9700 or +1.800.932-0624, Fax +1.908.329-9740, www.lindeus.com